

Coating composition comprising at least 3 components, process for its preparation, and its use

Patent Number: ☐ US6309707
Publication date: 2001-10-30
Inventor(s): MAYER BERND (DE); MEISENBURG UWE (DE); NIENHAUS EGBERT (DE)
Applicant(s):: BASF COATINGS AG (US)
Requested Patent: ☐ DE4421823
Application Number: US19960765609 19961220
Priority Number(s): DE19944421823 19940622
IPC Classification: C09D133/06 ; C09D167/02 ; C09D175/04
EC Classification: C08G18/08B6C, C08G18/10, C08G18/12, C08G18/40A12, C08G18/40A14, C08G18/42F,
C08G18/62G6D, C08G18/64F, C09D167/00, C09D175/04
Equivalents: BR9508098, CA2190286, ☐ EP0766717 (WO9535348), B1, ES2132684T,
JP10501838T, ☐ WO9535348

Abstract

The present invention relates to a coating composition comprising at least three components, characterized in that component (I) contains as binder at least one acrylate copolymer which is dissolved or dispersed in organic solvent and has a number-average molecular weight of between 1000 and 30,000, an OH number of from 40 to 200 and an acid number of from 5 to 150 and/or polyester resin having a number-average molecular weight of between 1000 and 30,000, an OH number of from 30 to 250 and an acid number of from 5 to 150 and/or polyurethane resin having a number-average molecular weight of between 1000 and 30,000, an OH number of from 20 to 200 and an acid number of from 5 to 150, and, if desired, a further binder, the binder components being selected such that a 50% strength solution of the binder in ethoxyethyl propionate has a viscosity at 23 C. of ≤ 2.5 dPa.s, component (II) contains at least one nonblocked polyisocyanate as crosslinking agent, and component (III) is essentially binder-free and contains water

Data supplied from the esp@cenet database - I2